

Ref. **9NACL10**

Indoor and dry environments

Low

Low shoes



S1P



The +

- * Value for money.
- * Reflective stripe.
- * PU2D injected outsole.
- * Defined and raised heel for better safety especially on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
9NACL10035	35	10
9NACL10036	36	10
9NACL10037	37	10
9NACL10038	38	10
9NACL10039	39	10
9NACL10040	40	10
9NACL10041	41	10
9NACL10042	42	10
9NACL10043	43	10
9NACL10044	44	10
9NACL10045	45	10
9NACL10046	46	10
9NACL10047	47	10
9NACL10048	48	10

Some sizes may only be available in certain countries

DESCRIPTION

NACRITE S1P is a low shoe that features an upper made of leather and polyurethane with a lining made of mesh. Its dual density PU/PU sole resists to hydrocarbons and to slip on ceramic and steel floors. It provides comfort to user. The reflective insert at the back improves safety of wearer when working in dark environment.

This model is equipped with a steel toe-cap and a steel plate for protection against puncture and fall of heavy objects.

NACRITE is the right model for any indoor use or in dry environment.

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
Electrician,
Storekeeper, ...

See also

VARIANTS



9NAC010

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	605 g	Closing	Lacing closure
Upper	Action leather / Polyurethane	Lining	Moisture wicking non-woven membrane
Toecap	Steel		
Puncture resistant sole	Stainless steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, perform a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/19/1523 EXT 01/04/20

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

SRC

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol