

Ref. **9RESL10**

Multipurpose

Low

Low shoes



### The +

- \*Soft PU/PU outsole: cushioning and comfort.
- \*Raised heel: stability on ladders.
- \*Wide cleats and flex lines: optimized adaptability to the ground.
- \*3D structured mesh upper: high abrasion resistance (laboratory tested).

### PURCHASE PACKAGING

Ref.	Size	Carton
9RESL10035	35	6
9RESL10036	36	6
9RESL10037	37	6
9RESL10038	38	6
9RESL10039	39	6
9RESL10040	40	6
9RESL10041	41	6
9RESL10042	42	6
9RESL10043	43	6
9RESL10044	44	6
9RESL10045	45	6
9RESL10046	46	6
9RESL10047	47	6
9RESL10048	48	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

CLAW RESIST is a lightweight, flexible and highly abrasion resistant safety sneaker.

This model has a resistant structured mesh upper, tested in a certified laboratory (CTC).

Its low density PU/PU outsole ensures all day comfort.

Its aluminum / composite protection system contributes to its sporty look.

### SECTORS

Light Industries

Regional/public authorities

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Light blue	Insole	PU Foam, removable, with shock absorber
Color 2	Dark grey	Reinforcement location	Front
Weight	545 g	Lining	Breathable 3D mesh
Upper	Mesh	Defined heel	
Toecap	Aluminium		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/22/1303

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

RETAILER STAMP