

Ref. 9FREL

Multipurpose

Low

Low shoes



The +

- * Footbridge supplying torsional rigidity.
- * Padding for snug fit.

PURCHASE PACKAGING

Référence	Taille	Carton
9FREL36	36	10
9FREL37	37	10
9FREL38	38	10
9FREL39	39	10
9FREL40	40	10
9FREL41	41	10
9FREL42	42	10
9FREL43	43	10
9FREL44	44	10
9FREL45	45	10
9FREL46	46	10
9FREL47	47	10
9FREL48	48	10

DESCRIPTION

Upper in granulated leather, water repellent
 External sole in PU double density
 Antipenetration textile sole, nonmagnetic
 Composite toecap, nonmagnetic
 Breathable textile lining

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
 Delivery driver, ...

TECHNICAL FEATURES

Color	Black	Lining	Breathable 3D mesh
Upper	Full grain leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		
Closing	Lacing closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The tim influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00361858**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EN ISO 20345:2011

S3

SRC

EPI CAT. II

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1MΩ < A < 1000 MΩ + Fuel and oil resistant contact outsole + Energy absorbing heel E ≥ 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP

MAJ 05/03/2021