

**Designation** : Fall Arrester on Polyamide Twisted Rope with energy absorbing lanyard

- Works on the anchor line *KRATOS SAFETY* in polyamide twisted rope, diametre 14-16 mm.
- Supplied with an energy absorber FA 30 000 45
- Simple opening / closing and automatic locking by a double security system.
- Has a manual locking position to allow work on inclined roof. (A)
- Has a unique non-inverting system to prevent from installing the device upside down on the anchor line. (B)
- Minimum breaking strength > 15 kN

**Connectors :**

1 steel screw-locking karabiner opening 17 mm, ref. FA 50 101 17 for connection on a harness.

**Compliance** : Conforms to EN 353-2 : 2002



**Material of the components :**

Rope Grab : Steel  
 Connector : Steel  
 Absorber : Polyester and polyamide

HS code	Carton Size / Pieces	Unit weight
83081010	40x40x24 / 20	1,20 kg

**AET : N° 2664 Issue 3 Extension 3**

Satra Technology Centre, N°0321  
 Wyndham Way, Telford Way, Kettering,  
 Northamptonshire, NN16 8SD, United Kingdom.

**Article 11: GB07/73551**

SGS United Kingdom Ltd., N° 0120  
 Unit 202B, Worle Parkway,  
 Weston-super-Mare, BS22 6WA, United Kingdom

 <small>MAJ : 02/15</small>	<p><b>ZI les portes du Dauphiné</b>  <b>4 rue de l'Aigue</b>  <b>69 780 St Pierre de Chandieu – France</b>  <b>Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32</b>  <b>www.kratossafety.com info@kratossafety.com</b></p>	
---	--	---