




## TECHNICAL SHEET FA 60 001 00

Tripod for access in confined spaces – Height maxi 2,15 m



	A	B	Ø
Mini	87 cm	78 cm	105 cm
Maxi	117 cm	101 cm	135 cm

Max. height:	CE	Weight :
2,15 m		13 kg

### KRATOS SAFETY

ZI les Portes du Dauphiné  
4, rue de l'Aigue  
69780 Saint Pierre de Chandieu – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

- With two mounted pulleys at the head of the Tripod in the extension of the main leg for passing a cable.
- Having two auxiliary eye bolts as attachment points.
- Aluminum alloy cast head, legs in aluminum.
- Steel support-shoes provided with rubber sole to increase friction and impart more stability
- **Strength of anchorage** point greater than > 12kN.
- Every Tripod is provided with inbuilt fixture for attaching our winch FA 60 003 00 (20 m) or FA 60 023 00 (30 m).
- Every Tripod is provided with Tripod Bag.
- **Compliance** : Conforms to EN 795:2012 Type B.

**Maximum load capacity** : 500 kg.

### Material of components :

Legs : Aluminium

Head : Aluminium alloy cast

Inbuilt fixture, support-shoes : Steel

### HS CODE

76109010

### CARTON SIZE / PIECES

148x30x28 / 1

### AET N° 2129 Issue 3 Extension 3

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering  
Northamptonshire, NN16 8SD, United Kingdom

### ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom