

Vented Helmet General Use



The +

Lightweight
Comfortable at hot temperatures:
sweatband of 37 cm
Side venting

PURCHASE PACKAGING

| Référence | Taille | Sachet | Carton |
|-----------|--------|--------|--------|
| 65105 | | | 24 |

SALES PACKAGING



Multiple

DESCRIPTION

- > Safety helmet
- > Shell and harness made of polyethylene
- > Adjustable (2 mm increments)
- > Sweatband 37 cm
- > Side venting
- > Average density 950 kg/m³
- > Weight : 370g

SECTORS

- Regional/public authorities
- Infrastructure, building industry
- Construction - finishing work
- Transport (excluding manufacturing) and logistics

APPLICATIONS

Construction works and industry

TECHNICAL FEATURES

| | | | |
|-----------------|---|---------------------|--|
| Color | Red | Service life | 60 months (as from manufacturing date displayed under the peak) |
| Color 2 | White | Main risk | Prevention from falling objects and head injuries or head trauma |
| Features | Polyethylene shell and harness 6 points suspension harness Adjustable size from 53 to 61cm (2mm increments) Manual size adjustment with a slide Compatible with earmuffs 60750 / 60755 / 60757 / 6MX3000NSI | | |
| Weight | 370 g | | |

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **2754/1747/158/06/19/0639**

Delivered by ALIENOR CERTIFICATION (2754) ZA du Sanital - 21- rue Albert Einstein - 86100 CHATELLERAULT - France



EPI CAT. II

EN397:2012+A1:2012

Industrial safety helmets

RETAILER STAMP